




Part No. 809401
FIREFLY LED BAR



Part No. 809403
FIREFLY LED BAR

FIREFLY LED BAR



PART NO.	809401	809403
VOLTAGE	10-48V DC	10-48V DC
CONSUMPTION	75 W	159 W
THEORETICAL LUMEN	6200	12 600
ACTUAL LUMEN	5010	10 670
1 LUX @	363 m	496 m
IP-CLASS	IP68	IP68
BEAM PATTERN	Combo	Combo
COLOR TEMPERATURE	6000K	6000K
POSITION LIGHT	White and amber	White and amber
CONNECTION	DT-4	DT-4
CABLE LENGTH	500 mm	500 mm
MATERIAL HOUSING	Aluminium	Aluminium
MATERIAL LENS	Polycarbonate	Polycarbonate
LENGTH	277 mm	515 mm
DEPTH	70 mm	70 mm
HEIGHT	38,5 mm	38,5 mm
HEIGHT INCLUDING BRACKET	51,5 / 56 mm	51,5 / 56 mm
OPERATING TEMPERATURE	-40°C - +65°C	-40°C - +65°C
E-APPROVED	ECE R149, R148	ECE R149, R148
REF	25	50
EMC-CERTIFICATE	ECE R10	ECE R10